

PCB TERMINAL BLOCKS

Top Entry Pluggable Terminal Blocks

- Vertical plug-in terminal blocks with wire entry inline with screw orientation
- Cage clamp connection
- Screw flange option
- Polarised mouldings mate with CTB93XX and CTB93XX/FL series headers

- Moulded in green UL94-V0 flame retardant PA66
- 0.2-2mm² (24-12AWG) stranded cable

SPECIFICATION

| | |
|-----------------------|-------------------------------|
| Rating | 16A/320V UL=300V, VDE=380V |
| Dielectric strength | 2kV |
| Insulation resistance | >2MΩ |
| Working temperature | -40°C to +105°C |
| Moulding | UL94-V0 flame retardant PA |
| Pin/terminal | Tinned phosphor bronze |
| Cage clamp | Nickel copper flash brass |
| Screw/torque | M3 steel zinc plated, 0.5Nm |

5mm, 5.08mm Vertical Top Entry Plug

5mm



| TYPE NO. | POLES | LENGTH |
|------------|-------|--------|
| CTB92TG/2 | 2 | 10mm |
| CTB92TG/3 | 3 | 15mm |
| CTB92TG/4 | 4 | 20mm |
| CTB92TG/5 | 5 | 25mm |
| CTB92TG/6 | 6 | 30mm |
| CTB92TG/7 | 7 | 35mm |
| CTB92TG/8 | 8 | 40mm |
| CTB92TG/9 | 9 | 45mm |
| CTB92TG/10 | 10 | 50mm |
| CTB92TG/11 | 11 | 55mm |
| CTB92TG/12 | 12 | 60mm |
| CTB92TG/13 | 13 | 65mm |
| CTB92TG/14 | 14 | 70mm |
| CTB92TG/15 | 15 | 75mm |
| CTB92TG/16 | 16 | 80mm |
| CTB92TG/17 | 17 | 85mm |
| CTB92TG/18 | 18 | 90mm |
| CTB92TG/19 | 19 | 95mm |
| CTB92TG/20 | 20 | 100mm |
| CTB92TG/21 | 21 | 105mm |
| CTB92TG/22 | 22 | 110mm |
| CTB92TG/23 | 23 | 115mm |
| CTB92TG/24 | 24 | 120mm |

5.08mm

| TYPE NO. | POLES | LENGTH |
|------------|-------|---------|
| CTB92TJ/2 | 2 | 10.2mm |
| CTB92TJ/3 | 3 | 15.2mm |
| CTB92TJ/4 | 4 | 20.3mm |
| CTB92TJ/5 | 5 | 25.4mm |
| CTB92TJ/6 | 6 | 30.5mm |
| CTB92TJ/7 | 7 | 35.6mm |
| CTB92TJ/8 | 8 | 40.6mm |
| CTB92TJ/9 | 9 | 45.7mm |
| CTB92TJ/10 | 10 | 50.8mm |
| CTB92TJ/11 | 11 | 55.9mm |
| CTB92TJ/12 | 12 | 61mm |
| CTB92TJ/13 | 13 | 66mm |
| CTB92TJ/14 | 14 | 71.1mm |
| CTB92TJ/15 | 15 | 76.2mm |
| CTB92TJ/16 | 16 | 81.3mm |
| CTB92TJ/17 | 17 | 86.4mm |
| CTB92TJ/18 | 18 | 91.4mm |
| CTB92TJ/19 | 19 | 96.5mm |
| CTB92TJ/20 | 20 | 101.6mm |
| CTB92TJ/21 | 21 | 106.7mm |
| CTB92TJ/22 | 22 | 111.8mm |
| CTB92TJ/23 | 23 | 116.8mm |
| CTB92TJ/24 | 24 | 121.9mm |

CTB92TG

CTB92TJ



5mm, 5.08mm Flanged Vertical Top Entry Plug

5mm

| TYPE NO. | POLES | LENGTH |
|--------------|-------|--------|
| CTB92TG/2FL | 2 | 20mm |
| CTB92TG/3FL | 3 | 25mm |
| CTB92TG/4FL | 4 | 30mm |
| CTB92TG/5FL | 5 | 35mm |
| CTB92TG/6FL | 6 | 40mm |
| CTB92TG/7FL | 7 | 45mm |
| CTB92TG/8FL | 8 | 50mm |
| CTB92TG/9FL | 9 | 55mm |
| CTB92TG/10FL | 10 | 60mm |
| CTB92TG/11FL | 11 | 65mm |
| CTB92TG/12FL | 12 | 70mm |
| CTB92TG/13FL | 13 | 75mm |
| CTB92TG/14FL | 14 | 80mm |
| CTB92TG/15FL | 15 | 85mm |
| CTB92TG/16FL | 16 | 90mm |
| CTB92TG/17FL | 17 | 95mm |
| CTB92TG/18FL | 18 | 100mm |
| CTB92TG/19FL | 19 | 105mm |
| CTB92TG/20FL | 20 | 110mm |
| CTB92TG/21FL | 21 | 115mm |
| CTB92TG/22FL | 22 | 120mm |
| CTB92TG/23FL | 23 | 125mm |
| CTB92TG/24FL | 24 | 130mm |

5.08mm

| TYPE NO. | POLES | LENGTH |
|--------------|-------|--------|
| CTB92TJ/2FL | 2 | 20.3 |
| CTB92TJ/3FL | 3 | 25.4 |
| CTB92TJ/4FL | 4 | 30.5 |
| CTB92TJ/5FL | 5 | 35.6 |
| CTB92TJ/6FL | 6 | 40.6 |
| CTB92TJ/7FL | 7 | 45.7 |
| CTB92TJ/8FL | 8 | 50.8 |
| CTB92TJ/9FL | 9 | 55.9 |
| CTB92TJ/10FL | 10 | 61.0 |
| CTB92TJ/11FL | 11 | 66.0 |
| CTB92TJ/12FL | 12 | 71.1 |
| CTB92TJ/13FL | 13 | 76.2 |
| CTB92TJ/14FL | 14 | 81.3 |
| CTB92TJ/15FL | 15 | 86.4 |
| CTB92TJ/16FL | 16 | 91.4 |
| CTB92TJ/17FL | 17 | 96.5 |
| CTB92TJ/18FL | 18 | 101.6 |
| CTB92TJ/19FL | 19 | 106.7 |
| CTB92TJ/20FL | 20 | 111.8 |
| CTB92TJ/21FL | 21 | 116.8 |
| CTB92TJ/22FL | 22 | 121.9 |
| CTB92TJ/23FL | 23 | 127.0 |
| CTB92TJ/24FL | 24 | 132.0 |

CTB92TG/FL

CTB92TJ/FL

