



# CAMBLOCK PLUS

## 7.5mm Pitch Commercial Low Profile Screw Terminal Blocks

PCB  
TERMINAL  
BLOCKS

- 2 & 3 pole
- Moulded in green UL94-V0 flame retardant PA66
- Wire protector terminals
- 2.5mm<sup>2</sup> (22-14AWG)
- Captive screws
- Anti solder wicking terminal
- Guided pin alignment
-  us &  approved

CTBP55VK



### SPECIFICATION

Rating	UL=16A/250V, VDE=24A/250V
Insulation resistance	500MΩ/500V
Withstand Voltage	AC2000V/1min
Contact Resistance	20mΩ (max)
Working Temperature	-40°C to 105+°C
Mouldings	UL94-V0 Flame retardant PA66
Pin/Terminal	Tin plated brass
Wire Protector	Phosphor bronze, nickel plated
Screw/Torque	M2.5 Steel, zinc plated 0.4Nm
Recommended PCB hole size	ø1.5mm

TYPE NO.	POLES	LENGTH
CTBP55VK/2	2	15mm
CTBP55VK/3	3	22.5mm
CTBP55VK/4	4	30mm
CTBP55VK/5	5	37.5mm
CTBP55VK/6	6	45mm
CTBP55VK/7	7	52.5mm
CTBP55VK/8	8	60mm
CTBP55VK/9	9	67.5mm
CTBP55VK/10	10	75mm
CTBP55VK/11	11	82.5mm
CTBP55VK/12	12	90mm

